

Econopak - Linkage Sprayer



Pictured: 300L Econopak

MODEL SPECIFICATIONS

PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and cast anodised aluminium body. BP60/20: 58 L/min. capacity 2000kPa pressure.
BOOM	Econopak boom: 6m with stainless steel spray lines, non-drip nozzle holders, fully galvanised frame and spring loaded safety break back/forward.
NOZZLES	Air induction nozzles with strainer in bayonet fit non-drip nozzle holders at 50cm spacings.
CONTROLS	3 outlet manual control valve with pressure regulator. Mounted forward for easy access.
TANK	Polytuff impact resistant polyethylene construction, moulded litre calibrations and non-spill screw-down lid with single breather.

FRAME	Fully galvanised steel, cat I & II linkage.			
AGITATION	Bypass agitation.			
PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.			
FILTRATION	Lid strainer, suction line strainer and nozzle strainers.			
HOSE REEL	Fitted with rear-mounted Eco hosereel, 30m of 10mm hose and Spotjet spraygun with adjustable spray nozzle.			
PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
KBC300 (WITH BOOM)	1105	2067	1070	116
KBC400 (WITH BOOM)	1105	2067	1310	121
KBC600 (WITH BOOM)	1200	2067	1400	151

MODEL DESCRIPTION

300L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom	CODE KBC300
400L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom	KBC400
600L ECONOPAK LINKAGE SPRAYER: BP60/20 pump, reel, hose & gun, 6m Econopak boom	KBC600

OPTIONS*

14L foam marker (single side)	CODE K99-31
16L foam marker (double side)	K99-39

*Note: Dealer fitment. \$500 charge applies for factory fitment.