RCR15 SERIES SINGLE SPINDLE ROTARY CUTTERS











Efficient handling and dispersing of material.

For small acreage owners looking for a heavier cutter, Land Pride offers the RCR1548. It features a 2" cutting capacity, a high blade tip speed, and larger gearbox than the RCR12. Ideal for maintenance of lanes, pastures, and other rough-cut areas.



Round back design helps discharge grass better than enclosed or partially enclosed cutters. The fully welded deck adds additional strength.



Two position floating top link offers greater lifting leverage for subcompact tractors, and allows deck to hug the terrain.



allows cutter to slide over obstructions protecting the gearbox output shaft.



Heavy-duty 1-1/4" spindle on the tailwheel gives strength to protect the tailwheel assembly.

	RCR1548
Horsepower	20-60 HP
Hitch	Cat. 1 & Cat. 1 Limited
Working Width (cm)	47-1/2" (121)
Overall Width	53-1/2"
Overall Length	91-3/4"
Weight - Ib (kg)	424 (192)
Cutting Height	1-3/4" - 11-1/2"
Cutting Capacity	2" Diameter
Deck Thickness	12 Gauge
Deck Height	7-1/4"
Safety Guards	Rubber Front and Rear
Skids	1/4" x 2" Weld On
Blades	1/2" x 3" Heat Treated Alloy Steel Free Swinging Blades
Blade Tip Speed	13,090 fpm
Dishpan	Round 10 Gauge x 24" Diameter, Dish Shaped
Gearbox Rating^	65 HP
Gearbox	540 RPM PTO Driven Gearbox Cast Iron Housing
Driveline	Cat. 3, Standard - 1/2" Shear Bolt Protection Optional - Bolt 2 Plate Slip Clutch
Tailwheel	4" x 16" Molded Rubber Tire
Colors	

